

EP Extreme Pressure & Lubricity Tester

(EP-2)

Overseas
Oil
Services



www.overseasoilservices.com



EP Extreme Pressure & Lubricity Tester (EP-2)

Overview

Used to measure the lubrication quality of drilling fluid; Provide data for evaluating the type and quantity of lubricating additives that may be required. It adopts frequency conversion technology and high-quality motor and driver. It has the characteristics of stepless speed regulation, compact structure, convenient operation and digital display of test data. It is widely used in oil fields, scientific research institutes, laboratories and other departments.

Technical parameter

- Acquisition, 230 Volt
- Belt-Driven Motor: 1/2 horsepower, 90 Volt DC, 5.5 Amps
- Maximum 600 inch-pounds of torque
- Shear rate: 1,000 RPM Maximum
- Fluid Pressure Range: 5,000 to 10,000 PSI (34,500-69,000 kPa)
- Size: 19" × 15" × 14" (48.3 × 38.1 × 35.6 cm)
- Weight: 56 lb (25.4 kg)
- Crated Size: 22" × 20" × 21" (56 × 51 × 53 cm)



- 325 N. St. Paul Street, Dallas, TX, 75201, USA.
- Sussex Centre, 90 Burnhamthorpe Road West, Suit 1400, Mississauga, Ontario, L5B 3C3, Canada.